01 / B75 · 75 cm HEMISPHERE · ROTATING LED DISPLAY

A new dimension for your story

Hemispherical holographic display | A planning reference for retail, showrooms and events.

FORM & STRUCTURE REFERENCE



FRONT VIEW



TOP VIEW

Transparent dome
Curved LED strips
Full-width circular base

75 cm

Listed display diameter

1536

Listed LED count

896 × 896

Listed content size / px

From the device to your project.

For selection and configuration review. Request exact-model raw photos, continuous playback footage in normal light and signed specifications before ordering.

02 / APPLICATION PLANNING

Content with a clear purpose

Suggested settings and content themes, not installed-project claims or playback simulations.

01



Retail & brand stores

Build a visual theme around perfume, jewellery or footwear. Keep one clear focal point.

02



Science & museums

Explore planetary, heritage or educational themes. Confirm content preparation and viewing requirements.


03



Corporate showrooms

Develop brand, product-story or launch themes. Test a short sequence using your actual assets.

04



Exhibitions & events

Plan launch, wedding or event visuals. Check placement, ambient light and power before deployment.

Planning tip: use the listed 750 × 750 × 400 mm envelope as a starting point. Confirm support, ventilation and service space separately.

03 / CONTENT MANAGEMENT

Choose a content workflow

Four workflows are listed in the supplied material. Confirm software, compatibility and service terms.

Mobile app

Android / iOS: confirm the app name, OS versions and connection steps.

Computer

Windows PC: confirm transfer, conversion and playback steps.

Cloud management

Confirm account access, network requirements and any service fees.

TF card

A 16 GB TF card is listed. Confirm media-conversion requirements.

LISTED FORMATS

MP4 / AVI / RMVB / GIF / JPG / PNG

AUDIO & SYNCHRONISATION: VERIFY SEPARATELY

Verify Bluetooth purpose, external speakers, auto-connect and audio sync. Check the actual configuration for DMX512 and multi-unit control.

Content template: 896 × 896 px is the listed production size, not physical resolution. Test conversion and playback with a short clip.

04 / PLACEMENT & INSTALLATION

Plan the space. Confirm the setup.

A project-planning guide, not a substitute for the exact-model installation manual.

LISTED UNIT ENVELOPE

750 × 750

Width × depth / mm

400 mm

Height · listed source value

Allow operating and service space

Confirm support dimensions, load capacity, fixing points, ventilation clearance, cable exit and adapter placement.

Table / display platform	Agree placement, fixing and service space with the manufacturer; check the complete cable route.
Pedestal / display cabinet	Verify support compatibility, stability and operating clearance. Supports are not assumed included.
Wall / suspended / side mounting	Obtain written confirmation of permitted orientation, load structure and fixing details for this model.

Request exact-model mounting drawings, power requirements and operating instructions before ordering. Unit dimensions do not define installation clearance.

05 / PACKING & DELIVERY


A clear delivery checklist

Quantities and packing data below are source-listed. Verify the actual shipment against the final order.

LISTED CARTON DIMENSIONS

950 × 950 × 600

mm



1 unit / carton

Gross approx. 10 kg

LISTED ITEMS IN THE BOX

Display unit	1
Power adapter	1
1 m figure-8 power cord	1
16 GB TF card	1
Remote control	1
User manual	1

External power is required; the source lists no internal battery. Confirm the market plug, electrical ratings, warranty and accessory appearance before ordering.

Listed packing: corrugated carton + EPE foam. Request photos of the actual inserts and full accessory set, plus pallet dimensions.

06 / ENQUIRY CHECKLIST

Brief the project clearly

Share these details with your sales contact to align configuration, prepare a sample clip and arrange a quotation.

01 Intended setting

☐ Retail, showroom or event; proposed position and ambient lighting.

02 Content requirements

☐ Logo, product images or video; whether content-production help is needed.

03 Delivery configuration

☐ Quantity, destination, plug, control method and support requirements.

04 Evidence before ordering

☐ Continuous footage of this exact model, confirmed specifications, accessory and packing photos.

Request exact-model footage and a confirmed configuration

Send the details above to your existing sales contact.

07 / TECHNICAL REFERENCE

Specifications at a glance

Source-listed values, not independent test results or signed specifications. Reconcile every value for this exact model.

ITEM	LISTED VALUE / STATUS
Model / SKU / market version	B75 (provisional); market version TBC
Product dimensions	750 × 750 × 400 mm
Display size / LED count	750 × 750 mm / 1536
Content size (not physical resolution)	896 × 896 px
Speed / brightness	700 rpm / 2000 cd/m²
Listed materials	ABS + PC / aluminium alloy
Processor / supplied storage card	ARM 1.2 GHz / 16 GB TF
File formats (conversion TBC)	MP4 / AVI / RMVB / GIF / JPG / PNG
Platforms / control	Windows PC / Android / iOS / Cloud / TF
Wireless / wired (scope TBC)	Wi-Fi 2.4G / Bluetooth 2.4G / DMX512
Finish (source terms to reconcile)	Nano coating / clear resin coating
Listed LED life (not a warranty)	> 30,000 hours; test conditions TBC
Input voltage / frequency / rated power	TO BE CONFIRMED
Retail pack / master carton / quantity	950 × 950 × 600 mm / 1 unit; pack level TBC
Net / gross weight	Net TBC / gross approx. 10 kg
Carton volume (calculated)	0.5415 m³ (cubic metres)
20GP / 40GP / 40HQ loading	TO BE CONFIRMED; not inferred from volume

ALSO CONFIRM BEFORE ORDERING

Adapter output, plug and market compliance; viewing coverage; audio and sync; mounting and cooling; software / cloud terms; packing levels and warranty.

PENDING MANUFACTURER VERIFICATION · NOT FOR CONTRACT USE